



ZEC S.p.A.

Via Lungolorno 11 - 42052 Colorno (PR) - Italia

Tel. 0521 816631 - Fax 0521 816772

info@zecspa.com - www.zecspa.com

Capitale sociale: Euro 1.000.000

C.F., P.IVA e n. Iscr. Reg. Imprese Parma: IT01720400348

Numero REA: PR - 173914

Jet Wash Hose JW Series Thermoplastic hose - Waterproof Cover*

- SUPER SLIDING AND ABRASION RESISTANT
- FLEXIBLE AND KINKING RESISTANT
- FOR MID-PRESSURE INDUSTRIAL AND GREENHOUSE CLEANING IN HORTICULTURE APPLICATIONS



WATER HANDLING



HIGH PRESSURE





WATER-BASED FLUIDS



WATER

TECHNICAL FEATURES

Metric

	 ID			 OD	 1:2.5 WP	 R MIN	 g	
Code	inch	mm	DN	mm	bar	mm	g/m	Ferrule Code
JW57109AR	3/8"	9.7	10	15.1	100	50	111	BP38R7V
JW67109AR	1/2"	12.5	12	18.5	100	80	150	BP12R7V
JW77109AR	5/8"	16.0	16	23.0	100	120	223	BP58R7V
JW87109AR	3/4"	19.2	19	26.6	100	180	272	BP34R7V

TECHNICAL FEATURES

Technical-constructive features:

Inner core in polyethylene, reinforcement in high tensile fiber braid and chemically bonded outside pin-pricked covering in anti-abrasion green polyurethane, stabilized to UV light, and resistant to microorganisms and hydrolysis for outdoor applications, in environments having high humidity levels.

Applications:

The JW series hoses have been developed for conveying water and detergents in mid-pressure industrial and greenhouse cleaning in horticulture applications.

Length variation:

+/- 1,5%

Working pressure:

Safety ratio: 1:2.5

Working temperature:

from -40° to +55°C (-40°F a +131°F).

*The water-proof feature of the cover means that the hose is especially suitable for wet and saline environments where there are extreme temperature changes.

OPTIONAL



Pin-pricking



Color



Cover



Multi-tube



Packing



Long Length

For any further information about the optional items, please contact the sales office ()